

TELEHANDLER

MVHT30.32

MVHT13510

Working height

31.5ft 10m

Load capacity

29765lbs 13500kg



MAVERICK


310 Edgewood Lane Cleburne Texas 76031

+1 786.340.6550


www.maverickmth.com

Load Chart

Machine on tires with forks LC 1200 mm Metric



Machine on tires with forks LC 600 mm Metric



Machine Parameters

System	Measurements	Imperial	Metric
Machine Parameters	Max. Lift Capacity	29,765lb	13,500kg
	Max. Lift Height	31.5ft	9,600mm
	Length(/with fork)	19.52/24.28ft	5,950/7,400mm
	Width	8.2ft	2,500mm
	Height	9.68ft	2,950mm
	Reach at Max Height	1.97ft	600mm
	Max. Forward Reach	17.06ft	5,200mm
	Operational Weight	45,360lb	20,575kg
	Ground Clearance	1.48ft	450mm
	Turning radius(outside)	17.06ft	5,200mm
Power System	Drive Speed	18.64mph	30km/h
	Gradeability(laden)	35%	
	Power Source	Cummins F 3.8	
	Emission Norm	Euro V	
Transmission System	Rated power	173hp	129kW
	Max. Torque	457lb.ft/1,500rpm	620Nm/1,500rpm
	Transmission mode	Hydrostatic Drive	
	Driving	4x4	
Tank Capacity	Steering Mode	2ws, Crab Steer, 4ws	
	Tires	17.5-25	
	Fuel Tank Capacity	61.59gal	280L
	Hydraulic Tank Capacity	65.99gal	300L

Various replaceable attachment

Installation of attachment adopts quick change mode,which can quickly switch attachments to achieve the operation requirement of different functions.

